




版次 (Vension)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/20A	630V/32A
压线范围 (Wire Range)	22~12AWG	4.0mm²
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	6~7mm	
工作温度 (Temperature)	-40℃~+105℃	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺丝 (Screws)	钢, 镀镍 (Steel, Nickel plating)	

产品命名编码:

(Product Number Code):

GSA45HW-9.5-XXP-1Y-00A (H)

产品型号 (Series No.)

客户需求

(Customer Request)

极数 (No. of poles)

塑体颜色 (Housing Color)

1: 单倍间距
(Single Pitch)
2: 双倍间距
(Double Pitch)

1: 绿色 (Green) 7: 透明色
(Transparent)
2: 蓝色 (Blue)
3: 黑色 (Black) 8: 白色 (White)
4: 灰色 (Grey) 9: 黄色 (Yellow)
5: 橙色 (Orange) Y: 多种颜色
6: 红色 (Red) (Mixed Color)

P=9.5mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~22P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P
L	38.00	47.50	57.00	66.50	76.00	85.50	95.00	104.50	114.00	123.50	133.00
B	9.50	19.00	28.50	38.00	47.50	57.00	66.50	76.00	85.50	95.00	104.50
N	13P	14P	15P	16P	17P	18P	19P	20P	21P	22P	
L	142.50	152.00	161.50	171.00	180.50	190.00	199.50	209.00	218.50	228.00	
B	114.00	123.50	133.00	142.50	152.00	161.50	171.00	180.50	190.00	199.50	

宁波高胜电子有限公司			公差范围 (Tolerance Range)	
GOOSVN NINGBO GOOSVN ELECTRONIC CO.,LTD			150~	±1.50
型号 (Type): GSA45HW-9.5-XXP-1Y-00A (H)			60~150	±1.00
核准 (Approval):			30~60	±0.60
图号 (Drawing NO.):			6~30	±0.30
审核 (Audit):			0~6	±0.25
单位 (Units): mm			角度 (Angle)	X ±2°
页码 (Page): 1/1			XX	±1°
设计 (Design):			比例 (Scale): FULL	版次 (Version): T0